

## TECHNICAL DATA SHEET

# TEKNOFIBRA

### APPLICATIONS:

product intended for those applications where heat absorption/reflection and sound absorption properties are required

### COMPOSITION

Available in below versions:

Aluminium + Teknofibra + Adhesive  
 Adhesive + Teknofibra + Adhesive  
 Aluminium + Teknofibra + Aluminium

Aluminium + Teknofibra  
 Adhesive + Teknofibra  
 Teknofibra

### INSTALLATION INSTRUCTIONS:

Using versions of Teknofibra with adhesive, be sure to clean the surface before apply the product.  
 Remove the protective liner only before application.

### HEAT CHARACTERISTICS:

Embosses 1200 aluminium surface	<b>657°C</b>
Adhesive	<b>-20°C+200°C</b>
Fibre:	<b>in excess of 400°C</b>
Complete product:	<b>in excess of 1000°C</b>

Weight: 2.5 mm thick +/- 410 gr./sqm ----- 4.0 mm thick +/- 570 gr./sq

### SAFETY NOTES:

Teknofibra **does not exhale any toxic fumes, even in high temperatures, and is NOT** harmful to health.

### NOTES:

It is the fitter's responsibility to develop specific application tests.  
 Manufacturer can not be considered responsible for a faulty use of the product.  
 Guarantee is expressly limited to the substitution of product if found faulty,  
 expressly excludes any other form of damage, indemnity or any other interest.